

CLAIMS

What is claimed is:

1. A method of forming a catalytic converter, the method comprising:
providing a catalytic converter having a central portion and an end portion,
wherein the central portion defines a horizontal central axis;
rotating the catalytic converter around the central axis;
placing a roller perpendicular to the central axis;
keeping the roller perpendicular to the central axis;
and forming the end portion by moving the roller in a transverse direction with
respect to the central axis.
2. The method of claim 1, further comprising the step of moving the roller
in a parallel direction with respect to the central axis.
3. The method of claim 1, wherein the end portion defines an axis at an
angle with respect to the central axis of the catalytic converter.
4. The method of claim 3, wherein the angle between the axis of the end
portion and the central axis is in the range of 30° to 60°.
5. The method of claim 1, wherein moving the roller in a transverse
direction with respect to the central comprises:
dividing the end portion into multiple imaginary planes perpendicular to the
central axis;
forming a contour corresponding to the multiple imaginary planes; and
programming the roller to follow the contour.
6. The method of claim 1, further comprising rotating the roller around an
axis parallel to the central axis.

SP102

TOP SECRET

SP102

SP102

SP102

SP 102
AAPA

SP 102

?

7. The method of claim 1, wherein the step of placing the roller comprises the step of contacting a surface of the catalytic converter such that moving the roller in the transverse direction reduces the diameter of the catalytic converter at the surface.

8. The method of claim 1, wherein forming the end portion further comprises cutting an end part of the end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.

9. A method of forming an end portion of a catalytic converter, the method comprising:

- providing a catalytic converter having a central portion and an end portion such that the central portion defines a horizontal central axis;
- rotating the catalytic converter around the central axis;
- placing a roller perpendicular to the central axis;
- keeping the roller perpendicular to the central axis; and
- moving the roller in a transverse direction with respect to the central axis, (wherein the end portion defines an axis at an angle with respect to the central axis.)

10. The method of claim 9, further comprising the step of moving the roller in a parallel direction with respect to the central axis.

11. The method of claim 9, wherein the angle between the axis of the end portion and the central axis is in the range of 30° to 60°.

12. The method of claim 9, wherein moving the roller in a transverse direction with respect to the central comprises:

- dividing the end portion into multiple imaginary planes perpendicular to the central axis;
- forming a contour corresponding to the multiple imaginary planes; and
- programming the roller to follow the contour.

FOR THE FSEE6560

JP 102

JP 102

JP
JP 102

JP of
AAPA

IR below
after
paving?

JP 103
13. The method of claim 9, rotating the roller around an axis perpendicular to the central axis.

14. The method of claim 9, wherein the step of placing the roller comprises contacting a surface of the catalytic converter such that moving the roller in the transverse direction reduces the diameter of the catalytic converter at the surface.

15. The method of claim 9, wherein forming the end portion further comprises cutting an end part of said end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.

16. A method of forming an oblique end portion of a catalytic converter, the method comprising:

providing a catalytic converter having a central portion and an end portion such that the central portion defines a horizontal central axis;

rotating the catalytic converter around the central axis;

placing one roller perpendicular to the central axis such that the roller contacts a surface of the end portion;

keeping the roller perpendicular to the central axis;

moving the roller in a transverse direction with respect to the central axis;

moving the roller in a transverse direction with respect to the central axis, such that the end portion defines an axis at an angle with respect to the central axis; and

reducing the diameter of the end portion in the surface .

17. The method of Claim 16, wherein the angle between the axis of the end portion and the central axis is in the range of 30° to 60°.

CONFIDENTIAL

JP 102

JP 103

JP 102

??

JP 102

SP
"HARA

18. The method of Claim 16, wherein moving the at least one roller in a transverse direction with respect to the central comprises:

dividing the end portion into multiple imaginary planes perpendicular to the central axis;

forming a contour corresponding to the multiple imaginary planes; and
programming the roller to follow the contour.

19. The method of claim 16, rotating the roller around an axis perpendicular to the central axis.

20. The method of claim 16, wherein forming the end portion further comprises cutting an end part of the end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.

FOR FTS2E660

103